



Metal Fastener Fabric – Data Sheet

PRODUCT DESCRIPTION

GAF Metal Fastener Fabric is a circular piece of fabric comprised of non-woven, stitch bonded polyester that is designed to reinforce the GAF Premium Acrylic HydroStop® System around metal fasteners.

Physical Properties¹

Outside Diameter	4 in (10.16 cm)
Insider Diameter	3/8 in (0.95 cm)
Weight	3 oz/yd ² (106.31 g/m ²)
Tensile Strength	MD: 70 lbs (56 kg) CD: 70 lbs (35 kg) [ASTM D5034]
Thickness	18 mils [ASTM D1777]
Elongation	MD: 25% CD: 104% [ASTM D5034]
Ball Burst	114 lbs (49 kg) [ASTM D3787]
Trapezoidal Tear	MD: 27 lbs (7.7 kg) CD: 19 lbs (9.1 kg) [ASTM D3787]

¹ Values are approximate and subject to normal manufacturing variations. These values are not guaranteed and are provided solely as a guide.

APPLICATION

INSTRUCTIONS

SURFACE PREPARATION: Apply Metal Roof Primer to all rusted fasteners and metal areas. Refer to Metal Roof Primer Data Sheet for coverage rate information.

APPLICATION: See instructions for the specific fabric-reinforced system being installed in the *Liquid-Applied Roofing Manual* at gaf.com.

WARRANTY

Refer to applicable warranties and guarantees, available at gaf.com, for complete coverage and restrictions.

PACKAGING SIZES

Each box contains 1,296 pieces.

SAFETY & HANDLING

For specific information regarding safe handling of this material, please refer to the Safety Data Sheet (SDS).

APPROVALS

State of Florida Approved	FL620 and FL20663
Miami-Dade Approved	NOA 20-0105.10

For application questions, contact GAF Technical Support Services at **1-877-GAF-ROOF**

We protect what matters most™

