



TRI-PLY®

SBS Granule Membrane (Formerly Tri-Ply® SBS Modified Bitumen)



Description

Tri-Ply® SBS Granule Membrane is a granule-surfaced modified bitumen membrane manufactured to stringent GAF specifications. Its core is a strong, resilient, non-woven polyester mat that is coated with flexible, SBS polymer-modified asphalt and is surfaced with mineral granules.

Uses

Tri-Ply® SBS Granule Membrane is designed for new roofing and reroofing applications, as well as flashings. Tri-Ply® SBS Granule Membrane is also an ideal product for repair of built-up roofing membranes or other modified bitumen systems. It can be installed with either hot asphalt or cold-applied adhesives.

Advantages

- Lightweight... installed roof designs weigh less than 2 pounds per square foot (9.8 kg per square meter).

Advantages (Continued)

- Resilient... polyester mat core allows it to resist splits and tears due to its pliability and elongation characteristics.
- Durable... specially formulated modified asphalt for lasting performance.

Applicable Standards

- Meets ASTM D6164, Type I, Grade G
- Miami-Dade County Product Control Approved
- FM Approved
- UL Listed

Nominal Specifications

Roll Size	1 square roll 107.5 gross sq. ft. (10.0 m ²)
Roll Length	32.6' (9.9 m)
Roll Width	39.6" (1.0 m)
Roll Weight	90 lb. (41 kg)