

PLAZA DECK SURFACING SYSTEM

PENETRATION METAL RAIN COLLAR

FLANGED METAL SLEEVE SET IN  
MODIFIED FLASHING CEMENT OR  
PARTIALLY MELTED SURFACE ON  
TORCH-APPLIED MEMBRANE.

RUBEROID® MEMBRANE TARGET



MIN 4" (102 mm) FLANGED PRIMED

RUBEROID® BASE/PLY SHEET

RUBEROID® FIELD MEMBRANE

**NOTE:**

1. THIS DETAIL SHOULD BE USED WITH LIGHT-GAUGE METALS THAT CAN BE FIELD-SOLDERED, SUCH AS 16 OUNCE COPPER, 24 GAUGE GALVANIZED STEEL, AND 25 GAUGE STAINLESS STEEL.
2. PENETRATION SLEEVE SHOULD EXTEND A MINIMUM OF 8" (203 mm) ABOVE TOP OF SURFACING.

 www.gaf.com 1 Campus Drive. Parsippany, NJ 07054	 Modified Bitumen Roofing Systems	<h2>FLANGED PENETRATION FLASHING</h2>	DRAWING # <h3>502</h3>	SYSTEM <h2>PD</h2>
	CUSTOM SERIES		SCALE N.T.S.	ISSUE/ REVISION DATE 8-08-14