

SAFETY DATA SHEET



1. Identification

Product identifier **UNITED COATINGS ROOF MATE BUTTER GRADE FLASHING**
UNITED COATINGS ROOF MATE FLASHING

Recommended use Elastomeric coating.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name GAF
1 Campus Drive
Parsippany, NJ 07054 USA

Telephone 1-800-766-3411

Emergency phone number CHEMTREC [DAY OR NIGHT] 1-800-424-9300
Within USA and CANADA 1-800-424-9300
Outside USA and Canada: 1 703-741-5970

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Sensitization, skin Category 1
Carcinogenicity Category 2
Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3
OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction. Suspected of causing cancer. Harmful to aquatic life.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist or vapor. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Calcium Carbonate		1317-65-3	30 to <40

Chemical name	Common name and synonyms	CAS number	%
PARAFFINIC PETROLEUM OIL		64742-54-7	1 to <5
TITANIUM DIOXIDE		13463-67-7	1 to <5
Aqua Ammonia (10-30%)		1336-21-6	0.1 to <1
CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER		10605-21-7	0.1 to <1
Chloro-2-methyl-4-isothiazolin-3-one		26172-55-4	0.1 to <1
Isobutane		75-28-5	0.1 to <1
Non-hazardous ingredients			60 to <70

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Upper respiratory tract irritation. Irritation of eyes and mucous membranes. Coughing. Skin irritation. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	If exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog, foam, dry chemical powder or carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	<p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.</p> <p>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.</p>

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Ammonium Hydroxide 20-30% (CAS 1336-21-6)	PEL	35 mg/m ³	
		50 ppm	
Calcium Carbonate (CAS 1317-65-3)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Ammonium Hydroxide 20-30% (CAS 1336-21-6)	STEL	35 ppm	
	TWA	25 ppm	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)	TWA	5 mg/m ³	Inhalable fraction.
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	10 mg/m ³	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Ammonium Hydroxide 20-30% (CAS 1336-21-6)	STEL	27 mg/m ³	
		35 ppm	
	TWA	18 mg/m ³	
		25 ppm	
Calcium Carbonate (CAS 1317-65-3)	TWA	5 mg/m ³	Respirable.
		10 mg/m ³	Total
Isobutane (CAS 75-28-5)	TWA	1900 mg/m ³	
		800 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment**Eye/face protection**

If contact is likely, safety glasses with side shields are recommended.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 8.07 lbs/gal

Percent volatile 30.63 %

Specific gravity 0.97

VOC < 50 g/L

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Fluorine.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes and mucous membranes. Upper respiratory tract irritation. Coughing. Skin irritation. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Components	Species	Test Results
------------	---------	--------------

Aqua Ammonia (10-30%) (CAS 1336-21-6)

Acute

Oral

LD50	Rat	350 mg/kg
------	-----	-----------

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7)

Acute

Dermal

LD50	Rabbit	> 2000 mg/kg
------	--------	--------------

	Rat	2000 mg/kg
--	-----	------------

Oral

LD50	Guinea pig	> 5000 mg/kg
------	------------	--------------

	Mouse	11000 mg/kg
--	-------	-------------

	Rat	> 5000 mg/kg
--	-----	--------------

Isobutane (CAS 75-28-5)

Acute

Inhalation

LC50	Mouse	52 mg/l, 1 Hours
------	-------	------------------

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

TITANIUM DIOXIDE (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not available.

Material name: UNITED COATINGS ROOF MATE BUTTER GRADE FLASHING
UNITED COATINGS ROOF MATE FLASHING

Version #: 03
SDS 3013

Revision date: 11-8-2017

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

Components	Species	Test Results
Aqua Ammonia (10-30%) (CAS 1336-21-6)		
Aquatic		
Fish	LC50	Western mosquitofish (<i>Gambusia affinis</i>) 15 mg/l, 96 hours
CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7)		
Aquatic		
Fish	LC50	Channel catfish (<i>Ictalurus punctatus</i>) 0.009 - 0.015 mg/l, 96 hours
TITANIUM DIOXIDE (CAS 13463-67-7)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) > 1000 mg/l, 48 hours
Fish	LC50	Mummichog (<i>Fundulus heteroclitus</i>) > 1000 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER	1.52
Isobutane	2.76

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chloro-2-methyl-4-isothiazolin-3-one (CAS 26172-55-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Aqua Ammonia (10-30%) (CAS 1336-21-6) Listed.
 CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7) Listed.
 Isobutane (CAS 75-28-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - No
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Aqua Ammonia (10-30%)	1336-21-6	0.1 to <1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Isobutane (CAS 75-28-5)

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Isobutane (CAS 75-28-5)
 PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)
 TITANIUM DIOXIDE (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Aqua Ammonia (10-30%) (CAS 1336-21-6)
 Calcium Carbonate (CAS 1317-65-3)
 Isobutane (CAS 75-28-5)
 TITANIUM DIOXIDE (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Aqua Ammonia (10-30%) (CAS 1336-21-6)
 Calcium Carbonate (CAS 1317-65-3)
 CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7)
 Isobutane (CAS 75-28-5)
 TITANIUM DIOXIDE (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Aqua Ammonia (10-30%) (CAS 1336-21-6)
 Calcium Carbonate (CAS 1317-65-3)
 Isobutane (CAS 75-28-5)
 TITANIUM DIOXIDE (CAS 13463-67-7)

US. Rhode Island RTK

Aqua Ammonia (10-30%) (CAS 1336-21-6)
 CARBAMIC ACID, 1H-BENZIMIDAZOL-2-YL, METHYL ESTER (CAS 10605-21-7)
 Isobutane (CAS 75-28-5)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

TITANIUM DIOXIDE (CAS 13463-67-7)

Diuron (CAS 330-54-1)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	12-10-2014
Revision date	11-8-2017
Version #	03
HMIS® ratings	Health: 2* Flammability: 0 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 0 Instability: 0

Disclaimer

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, **no representation, warranty or guarantee**, expressed or implied, **is made** as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. **We do not accept liability** for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

Revision Information

Product and Company Identification: Converted to GAF SDS