



GAF
Safety Data Sheet
SDS # 4066
SDS Date: July 2021

SECTION 1: PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: WOB Topcoat Acrylic Biocide-Free Top Coat
MANUFACTURER: GAF
ADDRESS: 1 Campus Drive, Parsippany, NJ 07054
24-HOUR EMERGENCY PHONE (CHEMTREC): 800 – 424 – 9300
INFORMATION ONLY: 800 – 766 – 3411
PREPARED BY: Corporate EHS
APPROVED BY: Corporate EHS

SECTION 2: HAZARD IDENTIFICATION

NFPA and HMIS RATINGS:

	NFPA Hazard Rating		HMIS Hazard Rating
Health	2	Health	2
Flammable	0	Flammable	0
Reactive	0	Reactive	0
Special Hazards	-	Personal Protection	X

GHS LABEL ELEMENTS:

GHS CLASSIFICATION: Eye Irritant - Category 2B
Skin Irritant - Category 2
Carcinogen - Category 2

GHS PICTOGRAMS:



SIGNAL WORD: Warning

HAZARD STATEMENTS: Causes mild skin irritation.
Causes eye irritation.
Suspected of causing cancer.

PRECAUTIONARY STATEMENTS:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Use personal protective equipment as required.
Wash face, hands and any exposed skin thoroughly after handling.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
IF EXPOSED OR CONCERNED: Get medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash before reuse.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

ADDITIONAL HAZARD IDENTIFICATION INFORMATION:

PRIMARY ROUTE OF EXPOSURE: Inhalation, Skin Contact, Eye Contact

SIGNS & SYMPTOMS OF EXPOSURE

EYES: Exposure to vapors can cause conjunctivitis or irritation to the eyes.

SKIN: Slight irritation of the skin. Prolonged contact can cause reddening of the skin.

INGESTION: Not expected to be ingested.

INHALATION: Vapors or mists can cause mental sluggishness, irritation of nasal passages, throat and lungs. Can cause headaches.

ACUTE HEALTH HAZARDS: Excessive exposure can cause pulmonary edema.

CHRONIC HEALTH HAZARDS: None known

CARCINOGENICITY: IARC has determined that occupational exposure to Titanium Dioxide is possibly carcinogenic to humans (Group 2B). IARC concluded lung tumors were observed in rats following high dose exposure by inhalation and in female rats exposed by intra-tracheal instillation. Other studies have shown no tumors in rats following inhalation exposure and no tumors in mice or rats following oral exposure.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	% (BY WT)	OCCUPATIONAL EXPOSURE LIMITS		
			OSHA	ACGIH	OTHER
Aluminum Trihydrate	21645-51-2	30 – 40	5 mg/m ³ – resp. 15 mg/m ³ – total	3 mg/m ³ – resp. 10 mg/m ³ – total	REL: 5 mg/m ³ – resp., 10 mg/m ³ – total
Titanium Dioxide	13463-67-7	5 – 10	15 mg/m ³ – total	10 mg/m ³ – total	REL: lowest feasible concentration
Zinc Oxide	1314-13-2	2 – 5	5 mg/m ³ – resp. 15 mg/m ³ – total	2 mg/m ³ – resp. 10 mg/m ³ – resp. STEL	REL: 5 mg/m ³ , 15 mg/m ³ – ceiling
Non-hazardous ingredients	-	45 – 60	NE	NE	NE

NE = Not Established

SECTION 4: FIRST AID MEASURES**FIRST AID PROCEDURES**

- EYES:** Flush eyes with water for 15 minutes. If irritation persists, call a physician.
- SKIN:** Wash the area thoroughly with soap and water.
- INHALATION:** Remove the person to an area that has fresh air. If breathing has stopped, administer artificial respiration. Contact physician immediately.
- INGESTION:** If the patient is awake, induce vomiting by giving two glasses of water and pressing down at back of throat. Call a physician immediately. Never give anything by mouth to an unconscious person.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: Excessive exposure can cause pulmonary edema.

SECTION 5: FIRE FIGHTING PROCEDURES

SUITABLE EXTINGUISHING MEDIA: Water spray, CO₂, Dry chemical or foam.

HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide and carbon monoxide.
RECOMMENDED FIRE FIGHTING PROCEDURES:	Self-contained breathing apparatus recommended.
UNUSUAL FIRE & EXPLOSION HAZARDS:	None

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES:	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Dam up area to prevent spreading. Caution – area will be slippery. Use absorbent material to dry up the compound.
-------------------------------------	--

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE:

Store in a well ventilated area at 50 – 80 °F. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment.

OTHER PRECAUTIONS:	Protect from freezing.
---------------------------	------------------------

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS / VENTILATION:	Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure limits.
RESPIRATORY PROTECTION:	If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection should be worn.
EYE PROTECTION:	Safety goggles or safety glasses with side shields.
SKIN PROTECTION:	Wear appropriate impermeable gloves and protective clothing as necessary to prevent skin contact.
General Hygiene Considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Control parameters

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR1910.1000)

Calcium Carbonate (CAS 1317-65-3)

PEL 5 mg/m3 Respirable fraction.
15 mg/m3 Total dust.

Titanium Dioxide (CAS 13463-67-7)

PEL 15 mg/m3 Total dust.

US. ACGIH Threshold Limit Values

Aluminum Trihydroxide (CAS 21645-51-2)

TLV 1 mg/m3 Respirable fraction.

Titanium Dioxide (CAS 13463-67-7)

TLV 10 mg/m3 Respirable fraction.

Zinc Oxide (CAS 1314-13-2)

TLV 10 mg/m3 Respirable fraction.

Appropriate engineering controls

- Showers
- Eyewash stations
- Adequate ventilation

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR:	Heavy white liquid with a slight ammonia odor.		
FLASH POINT:	> 240 °F	LOWER EXPLOSIVE LIMIT:	No data
METHOD USED:	TCC	UPPER EXPLOSIVE LIMIT:	No data
EVAPORATION RATE:	1.0	BOILING POINT:	212 °F
pH (undiluted product):	No data	MELTING POINT:	No data
SOLUBILITY IN WATER:	Dilutable in water	SPECIFIC GRAVITY:	1.48
VAPOR DENSITY:	No data	PERCENT VOLATILE:	No data
VAPOR PRESSURE:	No data	MOLECULAR WEIGHT:	No data
VOC (g/L):	<50		

SECTION 10: STABILITY AND REACTIVITY

THERMAL STABILITY:

STABLE X

UNSTABLE

CONDITIONS TO AVOID (STABILITY):	None known
INCOMPATIBILITY (MATERIAL TO AVOID):	Strong oxidizing agents.
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:	Carbon monoxide and carbon dioxide.
HAZARDOUS POLYMERIZATION:	Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Eye contact	Direct contact with the eyes may cause temporary irritation.
Skin contact	May cause slight skin irritation.
Ingestion	Expected to be a low ingestion hazard.

Information on toxicological effects

Aluminum Trihydroxide (CAS 21645-51-2)

Acute Oral Test Results

LD50 Rat > 5000 mg/kg

Zinc Oxide (CAS 1314-13-2)

Acute Inhalation

LC50 Mouse > 5.7 mg/l, 4 Hours

Oral LD50 Mouse 7950 mg/kg

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	This product is not expected to cause skin sensitization..
Germ cell mutagenicity	No information available.
Carcinogenicity	IARC has determined that occupational exposure to Titanium Dioxide is possibly carcinogenic to humans (Group 2B).
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

SECTION 12: ECOLOGICAL INFORMATION

Titanium Dioxide (CAS 13463-67-7)

Aquatic

EC50 Water flea (Daphnia magna) Mummichog (Fundulus heteroclitus) > 1000 mg/l, 48 hours

LC50 Fish Fathead minnow (Pimephales promelas) > 1000 mg/l, 96 hours

Zinc Oxide (CAS 1314-13-2)

Aquatic

LC50 Crustacea Fish

2246 mg/l, 96 hours

Persistence and degradability

Not readily biodegradable

Bioaccumulation

No information available.

Other adverse effects

No known significant or critical hazards.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Collect and reclaim or dispose in sealed containers at a licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

SECTION 14: TRANSPORTATION INFORMATION

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA: This product and its components are listed on the TSCA 8(b) inventory.

CERCLA: None.

SARA

311/312 HAZARD CATEGORIES: Acute Health Hazard, Chronic Health Hazard

313 REPORTABLE INGREDIENTS: None

CALIFORNIA PROPOSITION 65: This product can expose you to titanium dioxide which is known to the State of California to cause cancer.

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

Chemical Name	CAS #	CA	MA	MN	NJ	PA	RI
Aluminum Trihydrate	21645-51-2	No	No	No	No	No	No

Zinc Oxide	1314-13-2	Yes	No	Yes	Yes	Yes	Yes
Titanium Dioxide	13463-67-7	No	No	Yes	Yes	Yes	Yes

SECTION 16: OTHER INFORMATION

ADDITIONAL COMMENTS: None.

DATE OF PREVIOUS SDS: None.

CHANGES SINCE PREVIOUS SDS: New product.

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.